



NovoTouch BKxx2iw Series

Windows Interactive 4K-UHD Flat Panel wireless collaboration, Digital Whiteboard and Video Conferencing



Features:

Hardware:

- UltraHD 4K (3,840 × 2,160) resolution delivers exceptional clarity and impressive visual quality.
- 3mm-thick toughened glass enhances durability, providing protection against scratches and screen damage.
- Front bezel features USB-A and USB-C ports, facilitating convenient connections for USB peripherals such as keyboards, mice, memory drives, and data transfer.
- High-speed Wi-Fi 6 ensures seamless connectivity and efficient data transmission.
- Dual RJ45 ports enable straightforward Ethernet expansion for enhanced network connectivity.
- Built-in 13-megapixel camera and a 6-microphone array optimize video conferencing capabilities, ensuring clear and effective communication

Software:

- Windows-based wireless presentation and Video conferencing
- Digital Whiteboard for annotation
- Share your screen content with the participant
- Outlook Calendar integration
- Welcome banner and background image customization





NovoTouch

Specification:

	Model nan	ne	BK652i series	BKxx2iw series	
	Type/Techr	nology	Backlit D-LED (ADS Panel)		
Display	Panel Size		65" 75"		
	Brightness (Typ)		400cd/m2		
	Contrast Ratio (Typ)		1,200:1		
	Native Resolution		4K Ultra-HD (3840 x 2160)		
	Viewing Angle (H/V)		178°/178°		
	Aspect Ratio		16:9		
	Response Time (MS)		6ms		
	Refresh Rate (Hz)		60Hz		
	Estimated Life Time (Typ)		30,000 hours (Min)		
	Display Color (Bit)		1.07 billion (10-bit)		
	Installation Orientation		Landscape		
	Daily Operation (Hours/Days)		16/7		
	Technology		Infrared Touch		
	Touch	Writing	10 Point (Standard)		
	Points	Touch	20 Point (Standard)		
	Accuracy	Finger	±1mm (Over 90% area)		
Interactivity	Accuracy	Passive Pen	±1mm (Over 90% area)		
	Response Time		<10ms		
	Touch Resolution		32,768 x 32,768		
	Surface Protection		3mm Anti-Glare Thick Toughened Glass		
			(Level 7H on Mohs Scale of Mineral Hardness)		
	Touch Tools		Finger, Stylus, Glove, Opaque Objects		
System	CPU		Multi-Core High-Performance ARM [®] CPU		
	RAM		4GB DDR4		
	Internal Storage		32GB (eMMC Flash) (About 25GB User Availability)		
Connectivity	Input Output	Display	HDMI v2.0 (x3) Side, HDMI v2.0 (x1) Front		
		Audio	Mic(3.5mm)(x1)		
		Display	HDMI-Out v2.0 (x1) (up to 4K@60Hz)		
		Audio	Line-Out (3.5mm) (x1), SPDIF-Out (x1)		
			LAN (RJ45) (x2)		
	Wireless USB-A	Control	RS232-In (x1)		
		WiFi	IEEE802.11ax (2.4GHz/5GHz)		
		Bluetooth	BT 5.2		
		I/R Receiver	Front (x1) (±25° Angle, >8m Distance)		
		Front	USB 3.0 (x2)		
		Side	USB 3.0 (x2), USB 2.0 (x1)		
	USB-B USB-C	Front	USB Type B (x1) (For Touch Port)		
		Side	USB Type B (x1) (For Touch Port)		
		Front	USB-C (x1) (15W charging & display input)		
Expansion	Windows Module (Option) Standard Intel 80pin OPS (Option)				
	Speakers		18W (x2) (Stereo)		
Microphone		6 microphones array			
	Camera			Top-mounted 13Mega pixel, FOV: 120°, Focus length: 1~8m	
_	Power Supply (Internal)		AC 100 - 240V, 50/60Hz (4.5A)		
Power	Consumption (Tpy.) / Standby		130W, ≤0.5W (Standby)	140W, ≤0.5W (Standby)	
Physical Characteristics	VESA Mounting (FPMPMI)		600x400mm / 4-M8×25mm	800x400mm / 4-M8×25mm	
	Mini PC VESA Mount		100 x 2	· · · · · ·	
	Dimension (L x H x D)		1,484.5 x 90 x 908 mm	1705.7x90.2x1032.3 mm	
	Weight		39kg	50.8kg	
	-		, and the second s	*	
	Color Standard		Black / Silver AC Power Cord, Stylus (x2), Remote Control (W/Batteries), Wall Mount Kit, HDMI Cable(3M), Touch Cable(3M), WiFi Antenna(x3) Documentation Kit		
Accessories	Standard			M), WiFi Antenna(x3)	

©2024 Vivitek. Vivitek is a trademark of Delta Electronics, Inc. Other trademarks are the properties of their respective owners. Values, weights and dimensions shown are approximate. Errors and omissions accepted. Specifications are subjection to change without prior notice.

